

D3 72" TANDEM AXLE DUMP

STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

 INSIDE BED WIDTH: 72"	 DECK HEIGHT: 28"	 CARGO CAPACITY: 3.7 -8.9 yd³	 Dump Angle: 40°
 LENGTH: 10', 12'	 COUPLERS: Bumper Pull & Pintle	 AXLES: Tandem (2 x 5,200 lbs.)	 Choose optional ramps to increase the versatility of your dump trailer.
 GVWR: 9,900 lbs.	 LOAD CAPACITY: 6,970 - 7,240 lbs.	 DUMP SIDES HEIGHT: 20" (optional 48" sides)	



The Self-Contained Hydraulic Unit provides reliable power for your dump trailer, with standard power up/power down and gravity down operation to maximize dump cycles.

POWER UP/POWER DOWN & GRAVITY DOWN



Our UniWall Steel Technology uses form-rolled steel to add structural integrity, reduce corrosion-vulnerable seams, and lower the trailer weight to increase load capacity.

UNIWALL STEEL TECHNOLOGY



Enhance your trailer's versatility with our optional 2-Way Gate System, which combines the functionality of a barn door and spreader. This feature allows for maximum load dumping flexibility.

2-WAY GATE SYSTEM (OPTIONAL)



The Demco EZ Latch Coupler system makes hookup a breeze. You'll never have to fumble with complicated locking mechanisms or struggle to connect your trailer to your vehicle.

DEMCO EZ LATCH COUPLER

PJ TRAILERS

VISIT PJTRAILERS.COM FOR A COMPLETE LIST OF TRAILER OPTIONS.

PJ Trailers reserves the right to change price, design, material and/or specification without notice or obligation.